



SSC8L80GN6

N-Channel Enhancement Mode MOSFET

➤ Features

| V _{DS} | V _{GS} | R _{DS(ON)} Typ. | I _D |
|-----------------|-----------------|--------------------------|----------------|
| 80V | ±20V | 7.5mΩ@10V | 58A |
| | | 11mΩ@4V5 | |

➤ Description

This device is N-Channel enhancement MOSFET. Uses SGT technology and design to provide excellent RDSON with low gate charge. This device is suitable for use in DC-DC conversion, power switch and charging circuit.

100% UIS + ΔVDS + Rg Tested!

➤ Applications

- Motor Drive Control
- Synchronous rectification
- Power Management
- DC-DC Conversion


➤ Ordering Information

| Device | Package | Shipping |
|------------|------------|-----------|
| SSC8L80GN6 | PDFN5X6-8L | 5000/Reel |


➤ Pin configuration



PDFN5X6-8L



Pin Configuration (Top View)



Marking

(XX: product year / YY: product week)



➤ Absolute Maximum Ratings (T_A=25°C unless otherwise noted)

| Symbol | Parameter | Ratings | Unit | |
|------------------|---|-----------------------|------|---|
| V _{DSS} | Drain-to-Source Voltage | 80 | V | |
| V _{GSS} | Gate-to-Source Voltage | ±20 | V | |
| I _D | Continuous Drain Current ^d | T _C =25°C | 58 | A |
| | | T _C =100°C | 27 | |
| I _{DSM} | Continuous Drain Current ^a | T _A =25°C | 21 | A |
| | | T _A =70°C | 17 | |
| I _{DM} | Pulsed Drain Current ^b | 230 | A | |
| P _D | Power Dissipation ^c | T _C =25°C | 46 | W |
| | | T _C =100°C | 18.5 | |
| P _{DSM} | Power Dissipation ^a | T _A =25°C | 5.4 | W |
| | | T _A =70°C | 3.5 | |
| I _{AS} | Avalanche Current ^b L=0.5mH Single Pulse | 19 | A | |
| E _{AS} | Avalanche Energy ^b L=0.5mH Single Pulse | 90 | mJ | |
| T _J | Operation junction temperature | -55~150 | °C | |
| T _{STG} | Storage temperature range | -55~150 | | |

➤ Thermal Resistance Ratings (T_A=25°C unless otherwise noted)

| Symbol | Parameter | Ratings | Unit |
|------------------|---|---------|------|
| R _{θJA} | Junction-to-Ambient Thermal Resistance ^a | 23 | °C/W |
| R _{θJC} | Junction-to-Case Thermal Resistance | 2.7 | |

Note:


- The value of R_{θJA} is measured with the device mounted on 1 in² FR-4 board with 2oz.copper, in a still air environment with T_A=25°C. The value in any given application depends on the user is specific board design. The power dissipation is based on the t≤10s thermal resistance rating.
- Repetitive rating, pulse width limited by junction temperature.
- The power dissipation P_D is based on T_{J(MAX)}=150°C, using junction-to-case thermal resistance, and is more useful in setting the upper dissipation limit for cases where additional heat sinking is used.
- The maximum current rating is package limited.




➤ **Electrical Characteristics (T_A=25°C unless otherwise noted)**

| Parameter | Symbol | Test Conditions | Min. | Typ. | Max. | Unit |
|---------------------------------|----------------------|---|------|------|------|------|
| Drain-Source Breakdown Voltage | V _{(BR)DSS} | V _{GS} = 0V, I _D = 250μA | 80 | | | V |
| Gate Threshold Voltage | V _{GS(th)} | V _{DS} = V _{GS} , I _D = 250uA | 1.2 | 2 | 2.5 | V |
| Drain-Source On-Resistance | R _{DS(on)} | V _{GS} = 10V, I _D = 20A | | 7.5 | 10 | mΩ |
| | | V _{GS} = 4.5V, I _D = 10A | | 11 | 15 | |
| Zero Gate Voltage Drain Current | I _{DSS} | V _{DS} = 80V, V _{GS} = 0V | | | 1 | μA |
| Gate-Source Leak Current | I _{GSS} | V _{GS} = ±20V, V _{DS} = 0V | | | ±100 | nA |
| Transconductance | G _{FS} | V _{DS} = 5V, I _D = 20A | | 30 | | s |
| Forward Voltage | V _{SD} | V _{GS} = 0V, I _S = 10A | | 0.8 | 1.3 | V |
| Gate Resistance | R _G | V _{DS} = 0V, f = 1MHz | | 1.7 | | Ω |
| Input Capacitance | C _{ISS} | V _{DS} = 40V, V _{GS} = 0V, f = 1MHz | | 2117 | | pF |
| Output Capacitance | C _{OSS} | | | 506 | | |
| Reverse Transfer Capacitance | C _{RSS} | | | 56 | | |
| Total Gate Charge | Q _G | V _{GS} = 10V, V _{DS} = 40V, I _D = 20A | | 28 | | nC |
| Gate to Source Charge | Q _{GS} | | | 10 | | |
| Gate to Drain Charge | Q _{GD} | | | 5 | | |
| Turn-on Delay Time | T _{D(ON)} | V _{GS} = 10V, V _{DS} = 40V, R _L = 2Ω, R _G = 3Ω | | 9 | | ns |
| Rise Time | T _r | | | 5 | | |
| Turn-off Delay Time | T _{D(OFF)} | | | 23 | | |
| Fall Time | T _f | | | 8 | | |
| Diode Recovery Time | T _{rr} | I _F =20A, di/dt=500A/us | | 26 | | ns |
| Diode Recovery Charge | Q _{rr} | I _F =20A, di/dt=500A/us | | 120 | | nC |


➤ **Typical Performance Characteristics (T_A=25°C unless otherwise noted)**




Output Characteristics




Transfer Characteristics




On-Resistance vs. Drain Current and Gate Voltage



On-Resistance vs. Gate-to-Source Voltage




On-Resistance vs. Junction Temperature



Safe Operating Area, Junction-to-Ambient

➤ Package Information



| Symbol | Dimensions In Millimeters | | |
|--------|---------------------------|------|------|
| | Min. | Nom. | Max. |
| A | 0.90 | 1.00 | 1.10 |
| A1 | 0.00 | 0.03 | 0.05 |
| b | 0.25 | 0.03 | 0.35 |
| c | 0.254 REF | | |
| D | 4.80 | 4.90 | 5.00 |
| F | 1.35 REF | | |
| E | 5.65 | 5.75 | 5.85 |
| e | 1.27 BSC | | |
| H | 5.90 | 6.00 | 6.10 |
| L1 | 0.10 | 0.13 | 0.16 |
| G | 0.55 REF | | |
| K | 4.00 REF | | |
| J | 3.45 REF | | |



DISCLAIMER

SSCSEMI RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION OR DESIGN. SSCSEMI DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICIENCE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS.

THE GRAPHS PROVIDED IN THIS DOCUMENT ARE STATISTICAL SUMMARIES BASED ON A LIMITED NUMBER OF SAMPLES AND ARE PROVIDED FOR INFORMATIONAL PURPOSE ONLY. THE PERFORMANCE CHARACTERISTICS LISTED IN THEM ARE NOT TESTED OR GUARANTEED. IN SOME GRAPHS, THE DATA PRESENTED MAY BE OUTSIDE THE SPECIFIED OPERATING RANGE (E.G. OUTSIDE SPECIFIED POWER SUPPLY RANGE) AND THEREFORE OUTSIDE THE WARRANTED RANGE.

OUR PRODUCT SPECIFICATIONS ARE ONLY VALID IF OBTAINED THROUGH THE COMPANY'S OFFICIAL WEBSITE, CRM SYSTEM, OR OUR SALES PERSONNEL CHANNELS. IF CHANGES OR SPECIAL VERSIONS ARE INVOLVED, THEY MUST BE STAMPED WITH A QUALITY SEAL AND MARKED WITH A SPECIAL VERSION NUMBER TO BE VALID.