



SSC SSS52DA THRU SSC SSS520DA

Schottky Barrier Diode

● Features

- ✧ Reverse Voltage - 20 to 200 V
- ✧ Forward Current - 5.0A
- ✧ Low profile package
- ✧ Ideal for automated placement
- ✧ Ultrafast reverse recovery time
- ✧ Low power losses, high efficiency
- ✧ Low forward voltage
- ✧ High surge capability
- ✧ UL Flammability Classification Rating 94V-0
- ✧ High temperature soldering: 260°C/10 seconds at terminals

● PIN configuration



SMA/DO-214AC



Circuit Diagram



Marking

(SS54:SSC SSS54DA Marking Code)

● Applications


- ✧ Low Voltage
- ✧ High-Frequency Inverters
- ✧ Free Wheeling
- ✧ Polarity Protection

● Absolute maximum rating @T_A=25°C


Parameter	Symbol	SSCSSS								
		52DA	54DA	545DA	56DA	58DA	510DA	515DA	520DA	Unit
Maximum Peak Repetitive Peak Reverse Voltage	V _{RRM}	20	40	45	60	80	100	150	200	V
Maximum RMS Voltage	V _{RMS}	14	28	31.5	42	56	70	105	140	V
Maximum DC Blocking Voltage	V _{DC}	20	40	45	60	80	100	150	200	V
Maximum Average Forward Rectified Current	I _{F(AV)}	5.0								A
Non-repetitive Peak Forward Surge Current @t=8.3ms	I _{FSM}	120								A
Max Instantaneous Forward Voltage at 5 A	V _F	0.55			0.70	0.85		0.95		V
Maximum DC Reverse Current Ta = 25 ℃ at Rated DC Blocking Voltage Ta =125 ℃	I _R	0.2 10				0.05 5				mA
Operating Temperature	T _J	-55 ~ +125								℃
Storage Temperature	T _{STG}	-55 ~ +150								℃




● Typical Performance Characteristics




I_o -TL Curve



Surge Forward Current Capability Voltage



Typical Reverse Characteristics



Forward Voltage vs. Forward Current



● Package Information


Ordering Information

Device	Package	Marking	Qty per Reel	Reel diameters
SSCSSS52DA	SMA/DO-214AC	SS52	5000	11inch
SSCSSS54DA	SMA/DO-214AC	SS54	5000	11inch
SSCSSS545DA	SMA/DO-214AC	SS545	5000	11inch
SSCSSS56DA	SMA/DO-214AC	SS56	5000	11inch
SSCSSS58DA	SMA/DO-214AC	SS58	5000	11inch
SSCSSS510DA	SMA/DO-214AC	SS510	5000	11inch
SSCSSS515DA	SMA/DO-214AC	SS515	5000	11inch
SSCSSS520DA	SMA/DO-214AC	SS520	5000	11inch

Mechanical Data

Case: SMA/DO-214AC

Case Material: Molded Plastic. UL Flammability



DIM	Millimeters		
	Min	Nom	Max
A	1.40	1.50	1.60
B	2.50	2.67	2.90
C	4.00	4.40	4.50
D	2.00	2.25	2.45
E	0.05	0.200	0.203
F	0.76	1.14	1.52
G	-	-	0.203
H	4.90	5.0	5.30

Recommended Pad outline





DISCLAIMER

SSCSEMI RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION OR DESIGN. SSCSEMI DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICENCE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS.

THE GRAPHS PROVIDED IN THIS DOCUMENT ARE STATISTICAL SUMMARIES BASED ON A LIMITED NUMBER OF SAMPLES AND ARE PROVIDED FOR INFORMATIONAL PURPOSE ONLY. THE PERFORMANCE CHARACTERISTICS LISTED IN THEM ARE NOT TESTED OR GUARANTEED. IN SOME GRAPHS, THE DATA PRESENTED MAY BE OUTSIDE THE SPECIFIED OPERATING RANGE (E.G., OUTSIDE SPECIFIED POWER SUPPLY RANGE) AND THEREFORE OUTSIDE THE WARRANTED RANGE.

OUR PRODUCT SPECIFICATIONS ARE ONLY VALID IF OBTAINED THROUGH THE COMPANY'S OFFICIAL WEBSITE, CRM SYSTEM, OR OUR SALES PERSONNEL CHANNELS. IF CHANGES OR SPECIAL VERSIONS ARE INVOLVED, THEY MUST BE STAMPED WITH A QUALITY SEAL AND MARKED WITH A SPECIAL VERSION NUMBER TO BE VALID.