



## SSC8130GT8

### N-Channel Enhancement Mode MOSFET

#### ➤ Features

$V_{DS}$	$V_{GS}$	$R_{DS(ON)}$	$I_D$
30V	$\pm 20V$	3.5m $\Omega$ @10V	122A
		5m $\Omega$ @4.5V	

#### ➤ Description

This device is N-Channel enhancement MOSFET. Uses Trench technology and design to provide excellent RDSON with low gate charge. This device is suitable for use in DC-DC conversion, power switch and charging circuit.

**100% UIS +  $\Delta V_{DS}$  +  $R_g$  Tested!**


#### ➤ Applications

- DC/DC Converters
- Power Supplies
- Motor Drive Control
- Synchronous Rectification


#### ➤ Ordering Information

Device	Package	Shipping
SSC8130GT8	TO-252	2500/Reel


#### ➤ Pin Configuration



TO-252 (Top View)



Pin Configuration



Marking

(XYY: Internal Traceability Code)

**➤ Absolute Maximum Ratings ( $T_A=25^{\circ}\text{C}$  unless otherwise noted)**

Symbol	Parameter		Ratings	Unit
$V_{\text{DSS}}$	Drain-to-Source Voltage		30	V
$V_{\text{GSS}}$	Gate-to-Source Voltage		$\pm 20$	V
$I_{\text{D}}$	Continuous Drain Current <sup>d</sup>	$T_{\text{C}}=25^{\circ}\text{C}$	122	A
		$T_{\text{C}}=100^{\circ}\text{C}$	65	
$I_{\text{DSM}}$	Continuous Drain Current <sup>a</sup>	$T_{\text{A}}=25^{\circ}\text{C}$	38	A
		$T_{\text{A}}=70^{\circ}\text{C}$	28	
$I_{\text{DM}}$	Pulsed Drain Current <sup>b</sup>		488	A
$P_{\text{D}}$	Power Dissipation <sup>c</sup>	$T_{\text{C}}=25^{\circ}\text{C}$	78	W
		$T_{\text{C}}=100^{\circ}\text{C}$	31	
$P_{\text{DSM}}$	Power Dissipation <sup>a</sup>	$T_{\text{A}}=25^{\circ}\text{C}$	8.3	W
		$T_{\text{A}}=70^{\circ}\text{C}$	5.3	
$I_{\text{AS}}$	Avalanche Current <sup>b</sup> $L=0.5\text{mH}$ Single Pulse		25	A
$E_{\text{AS}}$	Avalanche Energy <sup>b</sup> $L=0.5\text{mH}$ Single Pulse		156	mJ
$T_{\text{J}}$	Operation junction temperature		-55~150	$^{\circ}\text{C}$
$T_{\text{STG}}$	Storage temperature range		-55~150	

**➤ Thermal Resistance Ratings ( $T_A=25^{\circ}\text{C}$  unless otherwise noted)**

Symbol	Parameter	Ratings	Unit
$R_{\theta\text{JA}}$	Junction-to-Ambient Thermal Resistance <sup>a</sup>	15	$^{\circ}\text{C}/\text{W}$
$R_{\theta\text{JC}}$	Junction-to-Case Thermal Resistance	1.6	

Note:


- The value of  $R_{\theta\text{JA}}$  is measured with the device mounted on 1 in<sup>2</sup> FR-4 board with 2oz.copper, in a still air environment with  $T_{\text{A}}=25^{\circ}\text{C}$ . The value in any given application depends on the user is specific board design. The power dissipation is based on the  $t \leq 10\text{s}$  thermal resistance rating.
- Repetitive rating, pulse width limited by junction temperature.
- The power dissipation  $P_{\text{D}}$  is based on  $T_{\text{J}(\text{MAX})}=150^{\circ}\text{C}$ , using junction-to-case thermal resistance, and is more useful in setting the upper dissipation limit for cases where additional heat sinking is used.
- The maximum current rating is package limited.

**➤ Electrical Characteristics (T<sub>A</sub>=25°C unless otherwise noted)**


Parameter	Symbol	Test Conditions	Min.	Typ.	Max.	Unit
Drain-Source Breakdown Voltage	V <sub>(BR)DSS</sub>	V <sub>GS</sub> = 0V, I <sub>D</sub> = 250μA	30			V
Gate Threshold Voltage	V <sub>GS(th)</sub>	V <sub>DS</sub> = V <sub>GS</sub> , I <sub>D</sub> = 250uA	1	1.5	2.5	V
Drain-Source On-Resistance	R <sub>DS(on)</sub>	V <sub>GS</sub> = 10V, I <sub>D</sub> = 20A		3.5	4.7	mΩ
		V <sub>GS</sub> = 4.5V, I <sub>D</sub> = 15A		5	6.8	mΩ
Zero Gate Voltage Drain Current	I <sub>DSS</sub>	V <sub>DS</sub> = 24V, V <sub>GS</sub> = 0V			1	μA
Gate-Source Leak Current	I <sub>GSS</sub>	V <sub>GS</sub> = ±20V, V <sub>DS</sub> = 0V			±100	nA
Transconductance	G <sub>FS</sub>	V <sub>DS</sub> = 5V, I <sub>D</sub> = 5A		14		s
Forward Voltage	V <sub>SD</sub>	V <sub>GS</sub> = 0V, I <sub>S</sub> = 10A		0.81	1.3	V
Input Capacitance	C <sub>ISS</sub>	V <sub>DS</sub> = 15V, V <sub>GS</sub> = 0V, f = 1MHz		2078		pF
Output Capacitance	C <sub>OSS</sub>			296		
Reverse Transfer Capacitance	C <sub>RSS</sub>			265		
Total Gate Charge	Q <sub>G</sub>	V <sub>GS</sub> = 10V, V <sub>DS</sub> = 15V, I <sub>D</sub> = 20A		38		nC
Gate to Source Charge	Q <sub>GS</sub>			8		
Gate to Drain Charge	Q <sub>GD</sub>			9.3		
Turn-on Delay Time	T <sub>D(ON)</sub>	V <sub>GS</sub> = 10V, V <sub>DS</sub> = 15V, R <sub>L</sub> = 1.5Ω, R <sub>G</sub> = 1Ω		11		ns
Rise Time	T <sub>r</sub>			68		
Turn-off Delay Time	T <sub>D(OFF)</sub>			94		
Fall Time	T <sub>f</sub>			53		
Diode Recovery Time	T <sub>rr</sub>	I <sub>F</sub> =20A, di/dt=100A/us		15		ns
Diode Recovery Charge	Q <sub>rr</sub>	I <sub>F</sub> =20A, di/dt=100A/us		6		nC




## ➤ Typical Performance Characteristics ( $T_A=25^\circ\text{C}$ unless otherwise noted)




Output Characteristics




Transfer Characteristics




On-Resistance vs. Drain Current and Gate Voltage



On-Resistance vs. Gate-to-Source Voltage




On-Resistance vs. Junction Temperature




Safe Operating Area vs. Junction-to-Ambient




## ➤ Package Information



SYMBOL	MILLIMETER		
	MIN	NOM	MAX
A	4.40	--	4.60
b	1.20	--	1.36
b1	0.70	--	0.90
C	0.48	--	0.53
C1	1.28	--	1.32
C2	0.04	0.12	0.20
D	9.80	10.00	10.20
D1	7.25	7.40	7.55
E	10.20	10.30	10.40
E1	9.10	9.20	9.30
e	--	2.54	--
L	4.70	4.90	5.10
L1	2.40	2.60	2.80
L2	1.50	1.70	1.90



T=0.5 ±0.1



### 技术要求:

1. 材料: 透明PVC
2. 表面电阻:  $10E5 \sim 10E10$  OHMS/SQ
3. 未注尺寸公差 $\pm 0.3$
4. 黑色钉子由厂家出货时塞于左端



---

## DISCLAIMER

SSCSEMI RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION OR DESIGN. SSCSEMI DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICENCE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS.

THE GRAPHS PROVIDED IN THIS DOCUMENT ARE STATISTICAL SUMMARIES BASED ON A LIMITED NUMBER OF SAMPLES AND ARE PROVIDED FOR INFORMATIONAL PURPOSE ONLY. THE PERFORMANCE CHARACTERISTICS LISTED IN THEM ARE NOT TESTED OR GUARANTEED. IN SOME GRAPHS, THE DATA PRESENTED MAY BE OUTSIDE THE SPECIFIED OPERATING RANGE (E.G. OUTSIDE SPECIFIED POWER SUPPLY RANGE) AND THEREFORE OUTSIDE THE WARRANTED RANGE.

OUR PRODUCT SPECIFICATIONS ARE ONLY VALID IF OBTAINED THROUGH THE COMPANY'S OFFICIAL WEBSITE, CRM SYSTEM, OR OUR SALES PERSONNEL CHANNELS. IF CHANGES OR SPECIAL VERSIONS ARE INVOLVED, THEY MUST BE STAMPED WITH A QUALITY SEAL AND MARKED WITH A SPECIAL VERSION NUMBER TO BE VALID.