



SSCS40101L6

Schottky Barrier Diode

● Features

- ✧ Small Surface Mounting Type
- ✧ Ideal for Automated Placement
- ✧ Ultrafast Reverse Recovery Time
- ✧ Low Power Losses, High Efficiency
- ✧ Low Forward Voltage Drop
- ✧ High Surge Capability
- ✧ RoHS Compliant
- ✧ UL Flammability Classification Rating 94V-0
- ✧ Moisture Sensitivity: Level 3 per J-STD-020

● PIN configuration




DFN1608-2L



Circuit Diagram

● Applications

- ✧ Low Voltage
- ✧ High-Frequency Inverters
- ✧ Free Wheeling
- ✧ Polarity Protection
- ✧ Switching circuit



Marking (Top View)

● Absolute maximum rating @T_A=25°C


Parameter	Symbol	Value	Unit
Reverse Voltage (Repetitive Peak)	V _{RRM}	40	V
Reverse Voltage (RMS)	V _{R(RMS)}	32	V
DC Blocking Voltage	V _R	40	V
Average Rectified Forward Current	I _O	1.5	A
Non-Repetitive Peak Forward Surge Current@ t=8.3ms	I _{FSM}	5	A
Power Dissipation	P _D	410	mW
Thermal Resistance Junction to Ambient (Typ)	R _{θJA}	305	°C/W
Operating Temperature	T _J	-55 ~ +150	°C
Storage Temperature	T _{STG}	-55 ~ +150	°C




● Electrical Characteristics @T_A=25°C

Parameter	Symbol	Conditions	Min.	Typ.	Max.	Unit
Breakdown Voltage	V _{BR}	I _R = 0.1mA	40			V
Reverse Current	I _R	V _R = 40V			20	μA
Total Capacitance	C _T	V _R = 10V, f = 1MHz			25	pF
Forward Voltage	V _F	I _F = 100mA		0.33	0.39	V
		I _F = 700mA		0.48	0.55	
		I _F = 1A		0.54	0.60	


● Typical Performance Characteristics



Forward Voltage vs. Forward Current



Reverse Voltage vs. Reverse Current



Power Derating vs. Lead Temperature



● Package Information


Ordering Information

Device	Package	Marking	Qty per Reel	Reel Size
SSCS40101L6	DFN1608-2L	S3	10000	7 Inch


Mechanical Data

Case: DFN1608-2L

Case Material: Molded Plastic. UL Flammability



Recommended Pad outline (Unit: mm)





DISCLAIMER

SSCSEMI RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION OR DESIGN. SSCSEMI DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICENCE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS.

THE GRAPHS PROVIDED IN THIS DOCUMENT ARE STATISTICAL SUMMARIES BASED ON A LIMITED NUMBER OF SAMPLES AND ARE PROVIDED FOR INFORMATIONAL PURPOSE ONLY. THE PERFORMANCE CHARACTERISTICS LISTED IN THEM ARE NOT TESTED OR GUARANTEED. IN SOME GRAPHS, THE DATA PRESENTED MAY BE OUTSIDE THE SPECIFIED OPERATING RANGE (E.G., OUTSIDE SPECIFIED POWER SUPPLY RANGE) AND THEREFORE OUTSIDE THE WARRANTED RANGE.

OUR PRODUCT SPECIFICATIONS ARE ONLY VALID IF OBTAINED THROUGH THE COMPANY'S OFFICIAL WEBSITE, CRM SYSTEM, OR OUR SALES PERSONNEL CHANNELS. IF CHANGES OR SPECIAL VERSIONS ARE INVOLVED, THEY MUST BE STAMPED WITH A QUALITY SEAL AND MARKED WITH A SPECIAL VERSION NUMBER TO BE VALID.