



SSCE3V311N7


Ultra Low Capacitance Array for ESD Protection

● Description


The SSCE3V311N7 provides a typical line to line capacitance of 0.3pF between I/O pins and low insertion loss up to 3.0GHz providing greater signal integrity making it ideally suited for HDMI applications, such as Digital TVs, DVD players, Computing, set-top boxes and MDDI applications in mobile computing devices.

It has been specifically designed to protect sensitive components which are connected to high-speed data and transmission lines from overvoltage caused by ESD(electrostatic discharge), CDE(Cable Discharge Events),and EFT (electrical fast transients).

● PIN configuration



Top view



Marking

● Feature

- ✧ 50W peak pulse power ($t_P = 8/20\mu s$)
- ✧ DFN2510-10L Package
- ✧ Working voltage: 3.3V
- ✧ Low clamping voltage
- ✧ Low capacitance
- ✧ RoHS compliant transient protection for high-speed data
- ✧ Complies with following standards:
 - IEC61000-4-2(ESD) $\pm 20kV$ (air),
 - IEC61000-4-2(ESD) $\pm 15kV$ (contact)

● Applications

- ✧ DVI & HDMI Port Protection
- ✧ Serial and Parallel Ports
- ✧ Projection TV
- ✧ Notebooks, Desktops, Server
- ✧ USB 1.1/2.0/3.0/3.1/OTG


● Mechanical data

- ✧ Lead finish:100% matte Sn (Tin)
- ✧ Mounting position: Any
- ✧ Qualified max reflow temperature:260°C
- ✧ Device meets MSL 3 requirements
- ✧ Pure tin plating: 7 ~ 17 μm
- ✧ Pin flatness: $\leq 3mil$



● Electronic Parameter

Symbol	Parameter
V_{RWM}	Peak Reverse Working Voltage
I_R	Reverse Leakage Current @ V_{RWM}
V_{BR}	Breakdown Voltage @ I_T
I_T	Test Current
I_{PP}	Maximum Reverse Peak Pulse Current
V_C	Clamping Voltage @ I_{PP}
P_{PP}	Peak Pulse Power
C_J	Junction Capacitance



● Absolute maximum rating @ $T_A=25^{\circ}\text{C}$

Parameter	Symbol	Value	Units
Peak Pulse Power (8/20 μs)	P_{PP}	50	W
Peak Pulse Current (8/20 μs)	I_{PP}	3.4	A
Storage Temperature	T_{STG}	-55/+150	$^{\circ}\text{C}$
Operating Temperature	T_J	-55/+150	$^{\circ}\text{C}$

● Electrical Characteristics @ $T_A=25^{\circ}\text{C}$


Parameter	Symbol	Conditions	Min.	Typ.	Max.	Units
Peak Reverse Working Voltage	V_{RWM}	Any I/O to GND			3.3	V
Breakdown Voltage	V_{BR}	$I_T = 1\text{mA}$ Any I/O to GND	3.8			V
Reverse Leakage Current	I_R	$V_{RWM} = 3.3\text{V}$			0.1	μA
Clamping Voltage	V_C	$I_{PP} = 1\text{A}$, $t_P = 8/20\mu\text{s}$		8		V
Clamping Voltage	V_C	$I_{PP} = 3.4\text{A}$, $t_P = 8/20\mu\text{s}$		10	13	V
ESD Clamping Voltage(Note1)	V_{CL-ESD}	IEC 61000-4-2+ 8kV($I_{TLP} = 16\text{A}$), contact mode, $T = 25^{\circ}\text{C}$, any I/O pin to GND		22		V
Dynamic resistance	R_{DYN}			0.75		Ω
Junction Capacitance	C_J	$V_R = 0\text{V}$, $f = 1\text{MHz}$, between I/O pins		0.3	0.4	pF
		$V_R = 0\text{V}$, $f = 1\text{MHz}$, any I/O pin to GND			0.8	pF

Note 1: ESD Clamping Voltage was measured by Transmission Line Pulsing (TLP) System.


TLP conditions: $Z_0 = 50\Omega$, $t_p = 100\text{ns}$, $t_r = 1\text{ns}$.




● Typical Performance Characteristics




Junction Capacitance vs. Reverse Voltage




Peak Pulse Power vs. Pulse Time




Clamping Voltage vs. Peak Pulse Current



Power derating vs. Ambient temperature



8/20us Pulse Waveform



Note: Data is taken with a 10x attenuator

Contact discharge current waveform

per IEC61000-4-2



● Package Information


Ordering Information

Device	Package	Qty per Reel	Reel Size
SSCE3V311N7	DFN2510-10L	3000	7 Inch

Mechanical Data


Case: DFN2510-10L

Case Material: Molded Plastic. UL Flammability




DIM	Millimeters	
	Min	Max
A	0.45	0.65
A1	0.05REF	
A2	0.15REF	
b	0.15	0.25
b1	0.30	0.50
D	2.424	2.576
E	0.924	1.076
e	0.50REF	
L	0.30	0.45

Recommended Pad outline




● Type and Reel Information-DFN2510-10L



(Unit: mm)

A0	B0	D0	D1	E	F	K0	P0
1.20±0.05	2.70±0.05	Φ1.55±0.05	Φ0.60±0.10	1.75±0.1	3.5±0.05	0.70±0.05	4.00±0.10
P1	P2	T	W				
4.00±0.10	2.00±0.05	0.25±0.05	8.00±0.05				





DISCLAIMER

SSCSEMI RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION OR DESIGN. SSCSEMI DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICENCE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS.

THE GRAPHS PROVIDED IN THIS DOCUMENT ARE STATISTICAL SUMMARIES BASED ON A LIMITED NUMBER OF SAMPLES AND ARE PROVIDED FOR INFORMATIONAL PURPOSE ONLY. THE PERFORMANCE CHARACTERISTICS LISTED IN THEM ARE NOT TESTED OR GUARANTEED. IN SOME GRAPHS, THE DATA PRESENTED MAY BE OUTSIDE THE SPECIFIED OPERATING RANGE (E.G. OUTSIDE SPECIFIED POWER SUPPLY RANGE) AND THEREFORE OUTSIDE THE WARRANTED RANGE.

OUR PRODUCT SPECIFICATIONS ARE ONLY VALID IF OBTAINED THROUGH THE COMPANY'S OFFICIAL WEBSITE, CRM SYSTEM, OR OUR SALES PERSONNEL CHANNELS. IF CHANGES OR SPECIAL VERSIONS ARE INVOLVED, THEY MUST BE STAMPED WITH A QUALITY SEAL AND MARKED WITH A SPECIAL VERSION NUMBER TO BE VALID.