



SSCE3V382N1

Ultra-low Capacitance Bidirectional Micro Packaged TVS Diodes for ESD Protection

● Description

The SSCE3V382N1 is designed with SSC Punch-Through process TVS technology to protect voltage sensitive components from ESD. Excellent clamping capability, low leakage, and fast response time provide best in class protection on designs that are exposed to ESD. Because of its small size, it is suited for use in cellular phones, MP3 players, digital cameras and many other portable applications where board space comes at a premium. Also because of its low capacitance, it is suited for use in high frequency designs such as USB 2.0 high speed, USB 4.0 super speed, VGA, DVI, HDMI, SDI and other high speed line applications.

It has been specifically designed to protect sensitive components which are connected to data and transmission lines from overvoltage caused by ESD (electrostatic discharge), and EFT (electrical fast transients).

● Feature

- ✧ Working voltage: 3.3V
- ✧ Low clamping voltage
- ✧ Low capacitance(0.35pF) for high-speed interfaces
- ✧ Low clamping voltage: VCL = 9.0V typ. @ IPP = 16A (TLP)
- ✧ Complies with following standards:
 - IEC 61000-4-2 (ESD) immunity test
 - Air discharge: $\pm 15\text{kV}$
 - Contact discharge: $\pm 15\text{kV}$
 - IEC61000-4-5 (Lightning) 3.5A (8/20 μs)


● Mechanical data

- ✧ Package: DFN1006-2L(1.0×0.6×0.5mm)
- ✧ Lead finish: 100% matte Sn (Tin)
- ✧ Device meets MSL 3 requirements
- ✧ Case Material: "Green" Molding Compound
- ✧ RoHS Compliant


● PIN configuration



DFN1006-2L (Bottom View)



Circuit Diagram



Marking


● Applications

- ✧ High Speed Line: USB1.0/2.0/3.0/4.0, VGA, DVI, SDI
- ✧ High Definition Multi-Media Interface (HDMI1.3/1.4/2.0)
- ✧ Serial and Parallel Ports
- ✧ Notebooks, Desktops, Servers
- ✧ Cellular handsets and accessories
- ✧ Portable instrumentation
- ✧ Peripherals



● Electronic Parameter

Symbol	Parameter
V_{RWM}	Peak Reverse Working Voltage
I_R	Reverse Leakage Current @ V_{RWM}
V_{BR}	Breakdown Voltage @ I_T
I_T	Test Current
I_{PP}	Maximum Reverse Peak Pulse Current
V_C	Clamping Voltage @ I_{PP}
P_{PP}	Peak Pulse Power
C_J	Junction Capacitance



● Absolute maximum rating @ $T_A=25^{\circ}\text{C}$

Parameter	Symbol	Value	Unit
Peak Pulse Power (8/20 μs)	P_{PP}	32	W
Peak Pulse Current (8/20 μs)	I_{PP}	3.5	A
ESD Rating per IEC61000-4-2: Contact Air	V_{ESD}	± 15 ± 15	kV
Storage Temperature	T_{STG}	-55/+150	$^{\circ}\text{C}$
Operating Temperature	T_J	-55/+125	$^{\circ}\text{C}$

● Electrical Characteristics @ $T_A=25^{\circ}\text{C}$


Parameter	Symbol	Conditions	Min.	Typ.	Max.	Unit
Peak Reverse Working Voltage	V_{RWM}				3.3	V
Breakdown Voltage	V_{BR}	$I_T = 1\text{mA}$	6.0	8		V
Reverse Leakage Current	I_R	$V_{RWM} = 3.3\text{V}$		1	50	nA
Clamping Voltage	V_C	$I_{PP} = 1\text{A}$, $t_P = 8/20\mu\text{s}$		3.6	5.5	V
Clamping Voltage	V_C	$I_{PP} = 3.5\text{A}$, $t_P = 8/20\mu\text{s}$		5.2	7	V
Clamping Voltage ¹⁾	V_{CL}	$I_{PP}=16\text{A}$, $t_P = 100\text{ns}$		9		V
Dynamic resistance ¹⁾	R_{DYN}			0.3		Ω
Clamping Voltage ²⁾	V_{CL}	$V_{ESD}=8\text{KV}$		9		V
Junction Capacitance	C_J	$V_R = 0\text{V}$, $f = 1\text{MHz}$		0.35	0.50	pF

Notes:


- 1) TLP parameter: $Z_0 = 50\Omega$, $t_p = 100\text{ns}$, $t_r = 2\text{ns}$, averaging window from 60ns to 80ns. R_{DYN} is calculated from 4A to 16A.
- 2) Contact discharge mode, according to IEC61000-4-2.
- 3) Non-repetitive current pulse, according to IEC61000-4-5.




● Typical Performance Characteristics




8/20μs Pulse Waveform




Peak Pulse Power vs. Pulse Time




Clamping voltage vs. Peak pulse current



Capacitance vs. Reverse voltage




Non-repetitive peak pulse power vs. Pulse time




Power derating vs. Ambient temperature




- Typical Performance Characteristics



ESD clamping
(+8kV contact discharge per IEC61000-4-2)



ESD clamping
(-8kV contact discharge per IEC61000-4-2)





● Package Information



Ordering Information

Device	Package	Qty per Reel	Reel Size
SSCE3V382N1	DFN1006-2L	10000	7 Inch

Mechanical Data


Case: DFN1006-2L

Case Material: Molded Plastic. UL Flammability



DIM	Millimeters		
	Min	Typ	Max
A	0.34	0.45	0.53
A1	0.00	0.02	0.05
A3	0.125REF		
D	0.95	1.00	1.08
E	0.55	0.60	0.68
b	0.45	0.5	0.55
L	0.20	0.25	0.3
e	0.65BSC		

Recommended Pad outline(Unit: mm)





DISCLAIMER

SSCSEMI RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION OR DESIGN. SSCSEMI DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICENCE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS.

THE GRAPHS PROVIDED IN THIS DOCUMENT ARE STATISTICAL SUMMARIES BASED ON A LIMITED NUMBER OF SAMPLES AND ARE PROVIDED FOR INFORMATIONAL PURPOSE ONLY. THE PERFORMANCE CHARACTERISTICS LISTED IN THEM ARE NOT TESTED OR GUARANTEED. IN SOME GRAPHS, THE DATA PRESENTED MAY BE OUTSIDE THE SPECIFIED OPERATING RANGE (E.G. OUTSIDE SPECIFIED POWER SUPPLY RANGE) AND THEREFORE OUTSIDE THE WARRANTED RANGE.

OUR PRODUCT SPECIFICATIONS ARE ONLY VALID IF OBTAINED THROUGH THE COMPANY'S OFFICIAL WEBSITE, CRM SYSTEM, OR OUR SALES PERSONNEL CHANNELS. IF CHANGES OR SPECIAL VERSIONS ARE INVOLVED, THEY MUST BE STAMPED WITH A QUALITY SEAL AND MARKED WITH A SPECIAL VERSION NUMBER TO BE VALID.