


SSCU10DN60GS1

Dual N-Channel Enhancement Mode MOSFET

➤ Features

V _{DS}	V _{GS}	R _{DSON} Typ.	I _D
60V	±20V	26mΩ@10V	10A
		30mΩ@4.5V	


➤ Pin Configuration



SOP-8

➤ Description

The SSCU10DN60GS1 uses advanced trench technology to provide excellent RDS(ON) and low gate charge. The complementary MOSFETs may be used to form a level shifted high side switch, and for a host of other applications.



Pin Configuration

➤ Applications

- Inverter
- DC-DC Converter
- Half and Full Bridge Topology



Marking

➤ Ordering Information

Device	Package	Shipping
SSCU10DN60GS1	SOP-8	4000/Reel

**➤ Absolute Maximum Ratings (T_A=25°C unless otherwise noted)**

Symbol	Parameter	Ratings	Unit
V _{DSS}	Drain-to-Source Voltage	60	V
V _{GSS}	Gate-to-Source Voltage	±20	V
I _D	Continuous Drain Current ^d	T _C =25°C	10
		T _C =100°C	5.2
I _{DM}	Pulsed Drain Current ^b	40	A
P _D	Power Dissipation ^c	T _C =25°C	3
		T _C =100°C	1.2
I _{AS}	Avalanche Energy ^b L=0.1mH Single Pulse	10.8	A
E _{AS}	Avalanche Energy ^b L=0.1mH Single Pulse	29	mJ
T _J	Operation junction temperature	-55~150	°C
T _{STG}	Storage temperature range	-55~150	

➤ Thermal Resistance Ratings (T_A=25°C unless otherwise noted)

Symbol	Parameter	Ratings	Unit
R _{θJA}	Junction-to-Ambient Thermal Resistance ^a	42	°C/W


Note:

- a. The value of R_{θJA} is measured with the device mounted on 1 in² FR-4 board with 2oz.copper, in a still air environment with T_A=25°C. The value in any given application depends on the user specific board design. The power dissipation is based on the t≤10s thermal resistance rating.
- b. Repetitive rating, pulse width limited by junction temperature.
- c. The power dissipation P_D is based on T_{J(MAX)}=150°C, using junction-to-case thermal resistance, and is more useful in setting the upper dissipation limit for cases where additional heat sinking is used.
- d. The maximum current rating is package limited.


➤ **Electrical Characteristics (T_A=25°C unless otherwise noted)**

Parameter	Symbol	Test Conditions	Min.	Typ.	Max.	Unit
Drain-Source Breakdown Voltage	V _{(BR)DSS}	V _{GS} = 0V, I _D = 250uA	60			V
Gate Threshold Voltage	V _{GS(th)}	V _{DS} = V _{GS} , I _D = 250uA	1	1.5	2.5	V
Drain-Source On-Resistance	R _{DS(on)}	V _{GS} = 10V, I _D = 6A		26	34	mΩ
		V _{GS} = 4.5V, I _D = 3A		30	42	
Zero Gate Voltage Drain Current	I _{DSS}	V _{DS} = 60V, V _{GS} = 0V			1	uA
Gate-Source Leak Current	I _{GSS}	V _{GS} = ±20V, V _{DS} = 0V			±100	nA
Forward Voltage	V _{SD}	V _{GS} = 0V, I _S = 5A		0.7	1.3	V
Input Capacitance	C _{ISS}	V _{DS} = 30V, V _{GS} = 0V, f = 1MHz		1375		pF
Output Capacitance	C _{OSS}			68		
Reverse Transfer Capacitance	C _{RSS}			62		
Total Gate Charge	Q _G	V _{GS} = 10V, V _{DS} = 30V, I _D = 5A		13		nC
Gate to Source Charge	Q _{GS}			3		
Gate to Drain Charge	Q _{GD}			6		
Turn-on Delay Time	T _{D(ON)}	V _{GS} = 10V, V _{DS} = 30V I _D = 4A, R _G = 3Ω		8.5		ns
Rise Time	T _r			15		
Turn-off Delay Time	T _{D(OFF)}			23		
Fall Time	T _f			4.2		
Diode Recovery Time	t _{rr}	IF=5A, dI/dt=100A/μs		29		ns
Diode Recovery Charge	Q _{rr}			42		nC


➤ **Typical Performance Characteristics ($T_A=25^\circ\text{C}$ unless otherwise noted)**




Output Characteristics




Transfer Characteristics




On-Resistance vs. Drain Current and Gate Voltage



On-Resistance vs. Gate-to-Source Voltage




On-Resistance vs. Junction Temperature



Safe Operating Area vs. Junction-to-Ambient

➤ **Package Information**



**DISCLAIMER**

SSCSEMI RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION OR DESIGN. SSCSEMI DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICENCE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS.

THE GRAPHS PROVIDED IN THIS DOCUMENT ARE STATISTICAL SUMMARIES BASED ON A LIMITED NUMBER OF SAMPLES AND ARE PROVIDED FOR INFORMATIONAL PURPOSE ONLY. THE PERFORMANCE CHARACTERISTICS LISTED IN THEM ARE NOT TESTED OR GUARANTEED. IN SOME GRAPHS, THE DATA PRESENTED MAY BE OUTSIDE THE SPECIFIED OPERATING RANGE (E.G. OUTSIDE SPECIFIED POWER SUPPLY RANGE) AND THEREFORE OUTSIDE THE WARRANTED RANGE.

OUR PRODUCT SPECIFICATIONS ARE ONLY VALID IF OBTAINED THROUGH THE COMPANY'S OFFICIAL WEBSITE, CRM SYSTEM, OR OUR SALES PERSONNEL CHANNELS. IF CHANGES OR SPECIAL VERSIONS ARE INVOLVED, THEY MUST BE STAMPED WITH A QUALITY SEAL AND MARKED WITH A SPECIAL VERSION NUMBER TO BE VALID.