

SSCE15V12N1

1-line Bidirectional Micro Packaged TVS Diodes for ESD Protection


● Description

The SSCE15V12N1 is a bi-directional TVS diode, utilizing leading monolithic silicon technology to provide fast response time and low ESD clamping voltage, making this device an ideal solution for protecting voltage sensitive data and power line. The SSCE15V12N1 complies with the IEC 61000-4-2 (ESD) with $\pm 30\text{kV}$ air and $\pm 30\text{kV}$ contact discharge.


● PIN configuration



DFN1006-2L (Bottom View)



Top View



Marking

● Feature

- ❖ 200W peak pulse power ($t_P = 8/20\mu\text{s}$)
- ❖ DFN1006-2L Package
- ❖ Working voltage: 15V
- ❖ Low clamping voltage
- ❖ Low capacitance
- ❖ Low leakage current
- ❖ Complies with following standards:
 - IEC61000-4-2(ESD) $\pm 30\text{kV}$ (contact),
 $\pm 30\text{kV}$ (air)
 - IEC61000-4-5(Lightning) 5A($8/20\mu\text{s}$)

● Applications


- ❖ Cellular Handsets and Accessories
- ❖ Personal Digital Assistants
- ❖ Notebooks and Handhelds
- ❖ Portable Instrumentation
- ❖ Digital Cameras
- ❖ Peripherals
- ❖ Audio Players
- ❖ Industrial Equipment

● Mechanical data

- ❖ Lead finish:100% matte Sn (Tin)
- ❖ Mounting position: Any
- ❖ Qualified max reflow temperature: 260°C
- ❖ Device meets MSL 3 requirements
- ❖ Pure tin plating: 7 ~ 17 um
- ❖ Pin flatness: $\leq 3\text{mil}$
- ❖ RoHS compliant

- **Electronic Parameter**

Symbol	Parameter
V_{RWM}	Peak Reverse Working Voltage
I_R	Reverse Leakage Current @ V_{RWM}
V_{BR}	Breakdown Voltage @ I_T
I_T	Test Current
I_{PP}	Maximum Reverse Peak Pulse Current
V_C	Clamping Voltage @ I_{PP}
P_{PP}	Peak Pulse Power
C_J	Junction Capacitance




- **Absolute maximum rating @ $T_A=25^\circ C$**

Parameter	Symbol	Value	Unit
Peak Pulse Power (8/20μs)	P_{PP}	200	W
Peak Pulse Current (8/20μs)	I_{PP}	5	A
ESD Rating per IEC61000-4-2:	V_{ESD}	30	kV
Contact Air		30	
Storage Temperature	T_{STG}	-55/+150	°C
Operating Temperature	T_J	-55/+125	°C


- **Electrical Characteristics @ $T_A=25^\circ C$**

Parameter	Symbol	Conditions	Min.	Typ.	Max.	Unit
Peak Reverse Working Voltage	V_{RWM}				15	V
Breakdown Voltage	V_{BR}	$I_T = 1mA$	15.6			V
Reverse Leakage Current	I_R	$V_{RWM} = 15V$			0.2	μA
Clamping Voltage	V_C	$I_{PP} = 1A, t_P = 8/20μs$		20		V
Clamping Voltage	V_C	$I_{PP} = 5A, t_P = 8/20μs$		30	40	V
Junction Capacitance	C_J	$V_R = 0V, f = 1MHz$		15	20	pF


- **Typical Performance Characteristics**




8/20μs Pulse Waveform



Peak Pulse Power vs. Pulse Time



Clamping Voltage vs. Peak Pulse Current



Power derating vs. Ambient temperature

- **Package Information**


Ordering Information

Device	Package	Qty per Reel	Reel Size
SSCE15V12N1	DFN1006-2L	10000	7 Inch


Mechanical Data

Case: DFN1006-2L

Case Material: Molded Plastic. UL Flammability



DIM	Millimeters	
	Min	Max
A	0.43	0.55
A1	0.00	0.05
D	0.55	0.65
E	0.95	1.05
b	0.45	0.60
e	0.65TYP	
L	0.2	0.3
L1	0.05REF	

Recommended Pad outline


**DISCLAIMER**

SSCSEMI RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION OR DESIGN. SSCSEMI DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICENCE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS.

THE GRAPHS PROVIDED IN THIS DOCUMENT ARE STATISTICAL SUMMARIES BASED ON A LIMITED NUMBER OF SAMPLES AND ARE PROVIDED FOR INFORMATIONAL PURPOSE ONLY. THE PERFORMANCE CHARACTERISTICS LISTED IN THEM ARE NOT TESTED OR GUARANTEED. IN SOME GRAPHS, THE DATA PRESENTED MAY BE OUTSIDE THE SPECIFIED OPERATING RANGE (E.G. OUTSIDE SPECIFIED POWER SUPPLY RANGE) AND THEREFORE OUTSIDE THE WARRANTED RANGE.

OUR PRODUCT SPECIFICATIONS ARE ONLY VALID IF OBTAINED THROUGH THE COMPANY'S OFFICIAL WEBSITE, CRM SYSTEM, OR OUR SALES PERSONNEL CHANNELS. IF CHANGES OR SPECIAL VERSIONS ARE INVOLVED, THEY MUST BE STAMPED WITH A QUALITY SEAL AND MARKED WITH A SPECIAL VERSION NUMBER TO BE VALID.