


## **SSCE5V032N1**

Ultra-low Capacitance Bidirectional Micro Packaged TVS Diodes for ESD Protection


### ● Description

The SSCE5V032N1 is a bi-directional TVS diode, utilizing leading monolithic silicon technology to provide fast response time and low ESD clamping voltage, making this device an ideal solution for protecting voltage sensitive high-speed data lines. The SSCE5V032N1 has an ultra-low capacitance with a typical value at 0.2pF, and complies with the IEC 61000-4-2 (ESD) with  $\pm 20\text{kV}$  air and  $\pm 20\text{kV}$  contact discharge. It is assembled into an ultra-small 1.0x0.6x0.5mm lead-free DFN package. Also because of its low capacitance, it is suited for use in high frequency designs such as USB 2.0 high speed, USB 3.0 super speed, VGA, DVI, HDMI, SDI and other high speed line applications.

### ● PIN configuration



Top view



Marking

### ● Applications

- ◊ DVI & HDMI Port Protection
- ◊ USB 2.0 and USB 3.0
- ◊ SATA and eSATA
- ◊ Serial and Parallel Ports
- ◊ Projection TV
- ◊ Notebooks, Desktops, Servers

### ● Feature


- ◊ 100W peak pulse power ( $t_P = 8/20\mu\text{s}$ )
- ◊ DFN1006-2L Package
- ◊ Working voltage: 5V
- ◊ Low clamping voltage
- ◊ Low capacitance
- ◊ Low leakage current
- ◊ RoHS compliant transient protection for high speed data lines to IEC61000-4-2(ESD) $\pm 20\text{kV}$ (air), $\pm 20\text{kV}$ (contact)

### ● Mechanical data

- ◊ Lead finish: 100% matte Sn(Tin)
- ◊ Mounting position: Any
- ◊ Qualified max reflow temperature:  $260^\circ\text{C}$
- ◊ Device meets MSL 3 requirements
- ◊ Pure tin plating: 7 ~ 17 um
- ◊ Pin flatness:  $\leq 3\text{mil}$

- **Electronic Parameter**

Symbol	Parameter
$V_{RWM}$	Peak Reverse Working Voltage
$I_R$	Reverse Leakage Current @ $V_{RWM}$
$V_{BR}$	Breakdown Voltage @ $I_T$
$I_T$	Test Current
$I_{PP}$	Maximum Reverse Peak Pulse Current
$V_C$	Clamping Voltage @ $I_{PP}$
$P_{PP}$	Peak Pulse Power
$C_J$	Junction Capacitance




- **Absolute maximum rating @ $T_A=25^\circ C$**

Parameter	Symbol	Value	Unit
Peak Pulse Power (8/20μs)	$P_{PP}$	100	W
Peak Pulse Current (8/20μs)	$I_{PP}$	4	A
ESD Rating per IEC61000-4-2:	$V_{ESD}$	20	kV
Contact Air		20	
Storage Temperature	$T_{STG}$	-55/+150	°C
Operating Temperature	$T_J$	-55/+125	°C


- **Electrical Characteristics @ $T_A=25^\circ C$**

Parameter	Symbol	Conditions	Min.	Typ.	Max.	Unit
Peak Reverse Working Voltage	$V_{RWM}$				5	V
Breakdown Voltage	$V_{BR}$	$I_T = 1mA$	6		9	V
Reverse Leakage Current	$I_R$	$V_{RWM} = 5V$			1	μA
Clamping Voltage	$V_C$	$I_{PP} = 1A, t_P = 8/20μs$		12		V
Clamping Voltage	$V_C$	$I_{PP}=4A, t_P = 8/20μs$			25	V
Junction Capacitance	$C_J$	$V_R=0V, f = 1MHz$		0.2	0.4	pF


- Typical Performance Characteristics




Junction Capacitance vs. Reverse Voltage




Peak Pulse Power vs. Pulse Time




Clamping Voltage vs. Peak Pulse Current



Power Derating Curve



8 X 20μs Pulse Waveform



Note: Data is taken with a 10x attenuator

ESD Clamping Voltage

8 kV Contact per IEC61000-4-2

## ● Package Information


### Ordering Information

Device	Package	Qty per Reel	Reel Size
SSCE5V032N1	DFN1006-2L	10000	7 Inch

### Mechanical Data


Case:DFN1006-2L

Case Material: Molded Plastic. UL Flammability




DIM	Millimeters	
	Min	Max
<b>A</b>	0.43	0.55
<b>A1</b>	0.00	0.05
<b>D</b>	0.55	0.65
<b>E</b>	0.95	1.05
<b>b</b>	0.45	0.60
<b>e</b>	0.65TYP	
<b>L</b>	0.2	0.3
<b>L1</b>	0.05REF	


### Recommended Pad outline




- Type and Reel Information-DFN1006-2L



DIM	Millimeters
	Typ
a	0.68
B	1.14
C	0.58
d	Φ 1.55
E	1.75
F	3.50
P0	4.00
P	2.00
P1	2.00
W	8.00



Pin 1 Quadrant: Q1&Q2



ΦA	ΦN	ΦB	C	W1	W2	W3
178mm	54mm	13.2mm	2.2mm	9.5mm	13 <sub>max</sub> mm	1.4mm

**DISCLAIMER**

SSCSEMI RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION OR DESIGN. SSCSEMI DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICENCE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS.

THE GRAPHS PROVIDED IN THIS DOCUMENT ARE STATISTICAL SUMMARIES BASED ON A LIMITED NUMBER OF SAMPLES AND ARE PROVIDED FOR INFORMATIONAL PURPOSE ONLY. THE PERFORMANCE CHARACTERISTICS LISTED IN THEM ARE NOT TESTED OR GUARANTEED. IN SOME GRAPHS, THE DATA PRESENTED MAY BE OUTSIDE THE SPECIFIED OPERATING RANGE (E.G. OUTSIDE SPECIFIED POWER SUPPLY RANGE) AND THEREFORE OUTSIDE THE WARRANTED RANGE.

OUR PRODUCT SPECIFICATIONS ARE ONLY VALID IF OBTAINED THROUGH THE COMPANY'S OFFICIAL WEBSITE, CRM SYSTEM, OR OUR SALES PERSONNEL CHANNELS. IF CHANGES OR SPECIAL VERSIONS ARE INVOLVED, THEY MUST BE STAMPED WITH A QUALITY SEAL AND MARKED WITH A SPECIAL VERSION NUMBER TO BE VALID.