



## SSCT7V021N1

### 1-Line Uni-directional TVS Diode

#### ● Description

The SSCT7V021N1 is an uni-directional TVS diode, utilizing leading monolithic silicon technology to provide fast response time and low ESD clamping voltage, making this device an ideal solution for protecting voltage sensitive data and power line. The SSCT7V021N1 complies with the IEC 61000-4-2 (ESD) with  $\pm 30\text{kV}$  air and  $\pm 30\text{kV}$  contact discharge.


#### ● Features

- ◇ Protects one I/O or Power Line
- ◇ DFN1006-2L Package
- ◇ Working voltage:7V
- ◇ Low Leakage Current
- ◇ Small Body Outline Dimensions
- ◇ Response Time is Typically<1ns
- ◇ Complies with following standards:
  - IEC61000-4-2(ESD)  $\pm 30\text{Kv}$ (contact),  
 $\pm 30\text{kV}$ (air)
  - IEC61000-4-4(EFT) 40A(5/50ns)
  - IEC61000-4-5(Lightning) 40A(8/20 $\mu\text{s}$ )

#### ● Mechanical Characteristics

- ◇ Package: DFN1006-2L
- ◇ Case Material: "Green" Molding Compound.
- ◇ UL Flammability Classification Rating 94V-0
- ◇ Moisture Sensitivity: Level 3 per-J-STD-020
- ◇ Terminal Connections: See Diagram Below
- ◇ Marking Information: See Below

#### ● PIN configuration



**Top view**



**Marking**


#### ● Applications

- ◇ Cellular Handsets and Accessories
- ◇ Personal Digital Assistants
- ◇ Notebooks and Handhelds
- ◇ Portable Instrumentation
- ◇ Digital Cameras
- ◇ Peripherals
- ◇ Audio Players
- ◇ Keypads, Side Keys, LCD Displays



● **Electronic Parameter**

Symbol	Parameter
$V_{RWM}$	Peak Reverse Working Voltage
$I_R$	Reverse Leakage Current @ $V_{RWM}$
$V_{BR}$	Breakdown Voltage @ $I_T$
$I_T$	Test Current
$I_{PP}$	Maximum Reverse Peak Pulse Current
$V_C$	Clamping Voltage @ $I_{PP}$
$P_{PP}$	Peak Pulse Power
$C_J$	Junction Capacitance



● **Absolute maximum rating @TA=25°C**


Parameter	Symbol	Value	Units
Peak Pulse Power (8/20μs)	$P_{PP}$	600	W
Peak Pulse Current (8/20μs)	$I_{PP}$	40	A
ESD Rating per IEC61000-4-2: Contact Air	$V_{ESD}$	±30 ±30	KV
Storage Temperature	$T_{STG}$	-55/+150	°C
Operating Temperature	$T_J$	-55/+125	°C

● **Electrical Characteristics @TA=25°C**


Parameter	Symbol	Conditions	Min.	Typ.	Max.	Units
Peak Reverse Working Voltage	$V_{RWM}$				7	V
Breakdown Voltage	$V_{BR}$	$I_T = 1mA$	7.5			V
Reverse Leakage Current	$I_R$	$V_{RWM} = 7V$			0.2	μA
Forward Voltage	$V_F$	$I_F = 10mA$			1.2	V
Clamping Voltage	$V_C$	$I_{PP} = 4A, t_P = 8/20μs$			9	V
Clamping Voltage	$V_C$	$I_{PP} = 40A, t_P = 8/20μs$			14	V
Junction Capacitance	$C_J$	$V_R = 0V, f = 1MHz,$		220		pF



● **Typical Performance Characteristics (TA=25°C unless otherwise Specified)**




**Junction Capacitance vs. Reverse Voltage**




**Peak Pulse Power vs. Pulse Time**

**Junction Capacitance vs. Reverse Voltage**


**Peak Pulse Power vs. Pulse Time**




**Clamping Voltage vs. Peak Pulse Current**



**Power Derating Curve**



**8 X 20μs Pulse Waveform**



**ESD Clamping Voltage**

**8 kV Contact per IEC61000-4-2**



## ● Package Information


### Ordering Information

Device	Package	Qty per Reel	Reel Size
SSCT7V021N1	DFN1006-2L	10000	7 Inch

### Mechanical Data


Case: DFN1006-2L

Case Material: Molded Plastic. UL Flammability



DIM	Millimeters	
	Min	Max
A	0.45	0.55
A1	0.00	0.05
D	0.55	0.65
E	0.95	1.05
b	0.45	0.60
e	0.65TYP	
L	0.2	0.3
L1	0.05REF	

### Suggested Land Pattern





## DISCLAIMER

SSCSEMI RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION OR DESIGN. SSCSEMI DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICIENCE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS.

THE GRAPHS PROVIDED IN THIS DOCUMENT ARE STATISTICAL SUMMARIES BASED ON A LIMITED NUMBER OF SAMPLES AND ARE PROVIDED FOR INFORMATIONAL PURPOSE ONLY. THE PERFORMANCE CHARACTERISTICS LISTED IN THEM ARE NOT TESTED OR GUARANTEED. IN SOME GRAPHS, THE DATA PRESENTED MAY BE OUTSIDE THE SPECIFIED OPERATING RANGE (E.G. OUTSIDE SPECIFIED POWER SUPPLY RANGE) AND THEREFORE OUTSIDE THE WARRANTED RANGE.

OUR PRODUCT SPECIFICATIONS ARE ONLY VALID IF OBTAINED THROUGH THE COMPANY'S OFFICIAL WEBSITE, CRM SYSTEM, OR OUR SALES PERSONNEL CHANNELS. IF CHANGES OR SPECIAL VERSIONS ARE INVOLVED, THEY MUST BE STAMPED WITH A QUALITY SEAL AND MARKED WITH A SPECIAL VERSION NUMBER TO BE VALID.